

End Emitting Optical fiber

Item	Diameter	Roll length	Attenuation	Package weight	Package Size	Picture
EEOF0.25	0.25mm	12000m	<300dB	3.0 kg	30*30*12cm	
EEOF0.50	0.50mm	6000m	<300dB	3.0 kg	30*30*12cm	
EEOF0.75	0.75mm	2700m	<300dB	3.0 kg	30*30*12cm	
EEOF1.0	1.0mm	1500m	<300dB	3.0 kg	30*30*12cm	
EEOF1.5	1.5mm	700m	<300dB	3.0 kg	30*30*12cm	
EEOF2.0	2.0mm	350 m	<300dB	3.0 kg	30*30*12cm	
EEOF3.0	3.0mm	150m	<300dB	3.0 kg	30*30*12cm	

Side Emitting Optical fiber

Item	Diameter	Roll length	Attenuation	Package weight	Package Size	Picture
SEOF0.75	0.75mm	2700m	<350dB	3.0 kg	30*30*12cm	
SEOF1.0	1.0mm	1500m	<350dB	3.0 kg	30*30*12cm	
SEOF1.5	1.5mm	700m	<350dB	3.0 kg	30*30*12cm	
SEOF2.0	2.0mm	350 m	<350dB	3.0 kg	30*30*12cm	

Sparkle Optical fiber

Item	Diameter	Roll length	Component	Package weight	Package Size	Picture
SPOF3*0.75	3.0mm	450m	3pc 0.75mm fiber &3.0m PVC tube	3.5 kg	25*25*30cm	
SPOF3*0.75W	3.5mm	450m	3pc 0.75mm fiber &1.0mm steel wire &3.5m PVC tube	7.0 kg	25*25*30cm	

Twisted Multi-core Side Emitting Optical Fiber

Item	Diameter	Roll length	Component	Package weight	Package Size	Picture
MSOF14*0.75	6.0mm	300m	14pc 0.75mm Endglow fiber	9.0 kg	40*40*30cm	
MSOF42*0.75	10.0mm	100m	42pc 0.75mm Endglow fiber	12.0 kg	40*40*30cm	
MSOF84*0.75	14.0mm	100m	84pc 0.75mm Endglow fiber	14.0 kg	40*40*30cm	
MSOF126*0.75	18.0mm	100m	126pc 0.75mm Endglow fiber	20.0 kg	40*40*30cm	



Soled side emitting Optical Fiber

Item	External Diameter (mm)	Internal Diameter (mm)	Description	Package Size (mm)	Picture
LSOF—1.5	1.5	1.5	Transparent	300*300*240	
LSOF—2.0	2	2	Transparent	300*300*240	
LSOF—2.0S	2	2	Super bright	300*300*240	
LSOF—2.5	2.5	2.5	Transparent	300*300*240	
LSOF—2.5S	2.5	2.5	Super bright	300*300*240	
LSOF—3.0	3	3	Transparent	300*300*240	
LSOF—3.0S	3	3	Super bright	300*300*240	
LSOF—4.0	4	4	Transparent	300*300*240	
LSOF—5.0	5	5	Transparent	300*300*240	
LSOF—5.0S	5	5	Super bright	300*300*240	
LSOF—6.0	6	6	Transparent	300*300*240	
LSOF—6.0S	6	6	Super bright	300*300*240	
LSOF—8.0	8	8	Transparent	300*300*240	
LSOF—10	10	10	Transparent	500*500*300	
LSOF—11	11	11	Transparent	500*500*300	
LSOF—12	12	12	Transparent	500*500*300	
LSOF—14	14	14	Transparent	500*500*300	
LSOF—14S	14	14	Super bright	500*500*300	
LSOF—16	16	16	Transparent	500*500*300	
LSOF—18	18	18	Transparent	500*500*300	
LSOF-iP—3.5	3.5	2	Transparent skin	500*500*300	
LSOF-iP—4	4	2.5	Transparent skin	500*500*300	
LSOF-iP—5	4.5	3	Transparent skin	500*500*300	
LSOF-iP—6	5	4	Transparent skin	500*500*300	
LSOF-iP—7	7	5	Transparent skin	500*500*300	
LSOF-iP—8.8	8.8	6	Transparent skin	500*500*300	
LSOF-iP—10	10	8	Transparent skin	500*500*300	
LSOF-iP—12	13	10	Transparent skin	500*500*300	
LSOF-iP—14	14	11	Transparent skin	500*500*300	
LSOF-iP—14	14	12	Transparent skin	500*500*300	
LSOF-iP—17.3	17.3	14	Transparent skin	500*500*300	
LSOF-iP—18	18	16	Transparent skin	500*500*300	
LSOF-iP—20	20	18	Transparent skin	500*500*300	



Black skin Emitting Optical Fiber					
Item	External Diameter (mm)	Internal Diameter (mm)	Description	Package Size (mm)	Picture
EFP—0.5	1	0.5	Black skin	300*300*240	
EFP—0.75	1.6	0.75	Black skin	300*300*240	
EFP—1.0	2.2	1	Black skin	300*300*240	
EFP—1.5	2.5	1.5	Black skin	300*300*240	
EFP—2.0	3	2	Black skin	300*300*240	
EFP—2.5	4	2.5	Black skin	300*300*240	
EFP—3.0	4.5	3	Black skin	300*300*240	
EFP—4.0	5	4	Black skin	300*300*240	
EFP—5.0	7	5	Black skin	300*300*240	
EFP—6.0	8.8	6	Black skin	300*300*240	
EFP—8.0	10	8	Black skin	300*300*240	
EFP—10	13	10	Black skin	500*500*300	
EFP—11	13	11	Black skin	500*500*300	
EFP—12	14	12	Black skin	500*500*300	
EFP—14	17.3	14	Black skin	500*500*300	

Sensory Optical Fiber Kit				
Item	Description	Package weight	Package Size	Picture
SOFK50*2	50pcs 2m 3*0.75mm Sparkle optical fiber	2kg	30*30*12cm	
SOFK100*1.5	100pcs 1.5m 3*0.75mm Sparkle optical fiber	2.5kg	30*30*24cm	
SOFK100*2	100pcs 2m 3*0.75mm Sparkle optical fiber	3.5kg	30*30*24cm	
SOFK100*3	100pcs 3m 3*0.75mm Sparkle optical fiber	5kg	30*30*24cm	
SOFK200*1.5	200pcs 1.5m 3*0.75mm Sparkle optical fiber	5kg	30*30*24cm	
SOFK200*2	200pcs 2m 3*0.75mm Sparkle optical fiber	6kg	30*30*24cm	
SOFK200*3	200pcs 3m 3*0.75mm Sparkle optical fiber	9kg	30*30*24cm	

Ceiling light kit				
Item	Description	Package weight	Package Size	Picture
BCK50*2	50pcs 2m Black End Emitting Optical fiber	3kg	30*30*12cm	
BCK100*1.5	100pcs 1.5m Black End Emitting Optical fiber	4.5kg	30*30*24cm	
BCK100*2	100pcs 2m Black End Emitting Optical fiber	5kg	30*30*24cm	
BCK100*3	100pcs 3m Black End Emitting Optical fiber	5.5kg	30*30*24cm	
BCK200*1.5	200pcs 1.5m Black End Emitting Optical fiber	8kg	30*30*24cm	
BCK200*2	200pcs 2m Black End Emitting Optical fiber	8.5kg	30*30*24cm	
BCK200*3	200pcs 3m Black End Emitting Optical fiber	9.5kg	30*30*24cm	

Bicycle Safety Light

Item	Color	Roll length	Light Length	Power time	Visibility	Picture
BSFF001B	Blue	240mm	100mm	100 Hrs Strobe&30 Hrs Constant	400meters	
BSFF002W	White	240mm	100mm	100 Hrs Strobe&30 Hrs Constant	400meters	
BSFF003P	Pink	240mm	100mm	100 Hrs Strobe&30 Hrs Constant	400meters	
BSFF004G	Green	240mm	100mm	100 Hrs Strobe&30 Hrs Constant	400meters	
BSFF005O	Orange	240mm	100mm	100 Hrs Strobe&30 Hrs Constant	400meters	
BSFF006Y	Yellow	240mm	100mm	100 Hrs Strobe&30 Hrs Constant	400meters	

LED light source

Picture	Item	LED Bulb	Standard (maximum) diameter (mm)	Description
	LLE-001	5-Φ5 20MA	5-Φ5.2	Five colors, Can be set color or flash or gradient, Built in multiple programs, Each program running speed can be adjusted
	LLE-003	1-5W	Φ14 (Φ17.3)	Six colors, Can set the color or continuous rotation, Color can change, Adjustable speed
	LLE-004	1-3X2W	Φ14 (Φ17.3)	RGB mixed color, a variety of procedures
	LLE-006	1-3X2W	Φ12 (Φ14)	RGB mixed color, a variety of procedures
	LLE-007	1-3W	Φ12 (Φ14)	Single color, red, green, blue, yellow, white
	LEA-501	1-5W	Φ14 (Φ17.3)	Six colors, Can set the color or continuous rotation, Color can change, Adjustable speed
	LEA-501DMX	1-5W	Φ14 (Φ17.3)	Six colors, DMX512 signal control, 3 DMX channels,Built in 22 procedures, Constant current source LED work is more stable. (CH1: color CH2: speed CH3: dimming)
	LEA-502	2-5W	2-Φ14 (Φ17.3)	Six colors, Can set the color or continuous rotation, Color can change, Adjustable speed
	LEB-321	1-3X2W	Φ14 (Φ17.3)	RGB mixed color
	LEB-321DMX	1-3X2W	Φ14 (Φ17.3)	Six colors, DMX512 signal control, 5 DMX channels,Built in 30 procedures, (CH1: red CH2: green CH3: blue CH4: speed CH5: dimming)
	LEB-322	2-3X2W	2-Φ14 (Φ17.3)	RGB mixed color



LED light source				
Picture	Item	LED Bulb	Standard (maximum) diameter (mm)	Description
	LEB-322DMX	2-3X2W	2-Φ14 (Φ17.3)	RGB mixed color, DMX512 signal control, 5 DMX channels, Built in 31 procedures, (CH1: red CH2: green CH3: blue CH4: speed CH5: dimming)
	LEC-302	2-3W	2-Φ14 (Φ17.3)	Six colors, Can set the color or continuous rotation, Color can change, Adjustable speed, Constant current source LED work is more stable.
	LEE-1001	1-10W	Φ14 (Φ17.3)	Six colors, Can set the color or continuous rotation, Color can change, Adjustable speed
	LEE-501DMX	1-5W	Φ14 (Φ17.3)	Six colors, Twinkle, Dimming
	LEE-1001DMX(I)	1-10W	2-Φ14 (Φ17.4)	Six colors, DMX512 signal control, 4 DMX channels, a variety of procedures, Constant current source LED work is more stable. (CH1: color CH2: color wheel speed CH3: dimming CH4: flash disk speed)
	LEE-1001DMX(II)	1-10W	Φ14 (Φ17.3)	Six Twinkle colors, DMX512 signal control, 4 DMX channels, a variety of procedures, Constant current source LED work is more stable. (CH1: color CH2: color wheel speed CH3: dimming CH4: flash disk speed)
	LEG-321	1-3X2W	Φ30	RGB mixed color, Built in 31 procedures, Constant current source LED work is more stable.
	LEF-502DMX	2-5W	2-Φ14 (Φ17.3)	Six Twinkle colors, DMX512 signal control, 6 DMX channels, 22 procedures, Constant current source LED work is more stable. (CH1: color CH2: color wheel speed CH3: dimming CH4: color CH5: color wheel speed CH6: dimming)
	LEH-3121DMX	1-3X12W	Φ30	RGB mixed color, Sound control, DMX512 signal control, 6 DMX channels, 24 procedures, (CH1: red CH2: green CH3: blue CH4: speed CH5: flash / built-in program speed CH6: built-in program)
	LEH-4091DMX	1-4X9W	Φ30	RGB mixed color, Sound control, DMX512 signal control, 8 DMX channels, 24 procedures, (CH1: red CH2: green CH3: blue CH4: CH5: speed CH7: total dimming CH6: flash / built in program speed CH8: built-in program)
	LEI-4091DMX	1-4X9W	Φ30	RGBW mixed color, DMX512 signal control, 8 DMX channels, a variety of procedures, (CH1: Red CH2: Green CH3: blue CH4: white CH5: speed CH6: dimming CH7: strobe CH8: flashing)
	LEI-4001	1-40W	Φ30	Six colors, Gradient or Set a color
	LEI-4001DMX	1-4X9W	Φ30	Six colors, Sound control, DMX512 signal control, 5 DMX channels, 14 procedures, (CH1 color: CH2 speed: CH3: empty CH4: dimming CH5: strobe), Overheat protection



LED light source

Picture	Item	LED Bulb	Standard (maximum) diameter (mm)	Description
	LEI-8001	1-90W	Φ30	Six colors, Gradient or Set a color
	LEI-8001DMX	1-90W	Φ30	Six colors, Sound control, DMX512 signal control, 5 DMX channels, 14 procedures, (CH1 color: CH2 speed: CH3: empty CH4: dimming CH5: strobe), Overheat protection
	LEJ-4001DMX	1-40W	Φ30	Six colors, Twinkle, Dimming
	LED-5W-ir	5w	Φ14	1. 24 keys IR remote controller ; 2. 12V power input; 3. 10m remote distance
	LED-5W-rf	5w	Φ14	1. 20 keys RF remote controller ; 2. 12V power input; 3. 8m remote distance
	LED-5W-IR-water proof	5w	Φ14	1. 24 keys IR remote controller ; 2. 12V safe power input; 3. 10m remote distance; 4. IP 67 water proof;
	LED-16W-8	16w	Φ20	1. 24 keys IR remote controller ; 2. 110V-240V power input; 3. 30 m remote distance
	LED-16W-IR	16w	Φ20	1. 24 keys IR remote controller ; 2. 110V-240V power input; 3. 10 m remote distance
	LED-16W-Rf	16w	Φ20	1. 20 keys RF remote controller ; 2. 110V-240V power input; 3. 12m remote distance
	LED-25W-IR	25w	Φ20	1. 24 keys IR remote controller ; 2. 110V-240V power input; 3. 10m remote distance 4. fan heat emission
	LED-25W-Rf	25w	Φ20	1. 20 keys RF remote controller ; 2. 110V-240V power input; 3. 12m remote distance 4. fan heat emission
	LED-32W-IR	2*32w	Φ20*2	1. 24 keys IR remote controller ; 2. 110V-240V power input; 3. 10m remote distance 4. fan heat emission










LED light source


Picture	Item	LED Bulb	Standard (maximum) diameter (mm)	Description
	LED-32W-Rf	2*32w	Φ20*2	1. 20 keys RF remote controller ; 2. 110V-240V power input; 3. 12m remote distance 4. fan heat emission
	LED-35W-IR	2*35w	Φ20*2	1. 24 keys IR remote controller ; 2. 110V-240V power input; 3. 10m remote distance 4. fan heat emission
	LED-35W-Rf	2*35w	Φ20*2	1. 20 keys RF remote controller ; 2. 110V-240V power input; 3. 12m remote distance 4. fan heat emission
	LED-7W-Rf	7w	Φ14	1. 10 keys RF remote controller ; 2. 110V-240V power input; 3. 8m remote distance
	LED-7W-Rf-car	7w	Φ14	1. 10 keys RF remote controller ; 2. 110V-240V power input; 3. 8m remote distance
	LED-27W-IR	27w	Φ30	1. 24 keys IR remote controller ; 2. 110V-240V power input; 3. 10m remote distance 4. twinkle star or shooting star
	LED-27W-RF	27w	Φ30	1. 20 keys RF remote controller ; 2. 110V-240V power input; 3. 12m remote distance 4. twinkle star or shooting star
	LED-45W-IR	45w	Φ30	1. 24 keys IR remote controller ; 2. 220V-240V power input; 3. 10m remote distance
	LED-45W-RF	45w	Φ30	1. 20 keys RF remote controller ; 2. 220V-240V power input; 3. 12m remote distance
	LED-75W-IR	75w	Φ30	1. 24 keys IR remote controller ; 2. 220V-240V power input; 3. 10m remote distance 4. fan heat emission
	LED-75W-RF	75w	Φ30	1. 20 keys RF remote controller ; 2. 220V-240V power input; 3. 12m remote distance 4. fan heat emission



LED light source





























Picture	Item	LED Bulb	Standard (maximum) diameter (mm)	Description
	LED-120-ir	120w	Φ30	1. 24 keys IR remote controller ; 2. 220V-240V power input; 3. 10m remote distance 4. fan heat emission
	led-120-rf	120w	Φ30	1. 20 keys RF remote controller ; 2. 220V-240V power input; 3. 12m remote distance 4. fan heat emission
	LED-6H-RF	6w	Φ30	1. twinkle star effect ; 2. shooting star effect; 3. 12m remote distance 4. 20 key remote
	led-7w-rf	7w	Φ30	1. color wheel speed tunable ; 2. several light effect; 3. 12m remote distance 4. 20 key remote
	led-20w-rf	20w	Φ30	1. 20 keys RF remote controller ; 2. 12V power input; 3. 12m remote distance
	LED-5W-ir	5w	Φ14	1. 24 keys IR remote controller ; 2. 12V power input; 3. 10m remote distance
	LED-5W-rf	5w	Φ14	1. 20 keys RF remote controller ; 2. 12V power input; 3. 8m remote distance

FRP













Model	Dia.of fiber	Length of fiber	Pcs of fiber	Light source	Picture
FRP-01	0.75mm	2m	150	LED-6W-IR	
FRP-02	0.75mm	2m	150	LED-6W-RF	
FRP-03	0.75mm	2m	200	LED-6W-IR	
FRP-04	0.75mm	2m	200	LED-6W-RF	
FRP-05	0.75mm	3m	250	LED-6W-IR	
FRP-06	0.75mm	3m	250	LED-6W-RF	



BCLIGHT fiber optic lighting

			
BCLIGHT-001	BCLIGHT-002	BCLIGHT-003	BCLIGHT-004
			
BCLIGHT-005	BCLIGHT-006	BCLIGHT-007	BCLIGHT-008
			
BCLIGHT-009	BCLIGHT-010	BCLIGHT-011	BCLIGHT-012
			
BCLIGHT-013	BCLIGHT-014	BCLIGHT-015	BCLIGHT-016
			
BCLIGHT-017	BCLIGHT-018	BCLIGHT-019	BCLIGHT-020
			
BCLIGHT-021	BCLIGHT-022	BCLIGHT-023	BCLIGHT-024
			
BCLIGHT-025	BCLIGHT-026	BCLIGHT-027	BCLIGHT-028



			
BCLIGHT-029	BCLIGHT-030	BCLIGHT-031	BCLIGHT-032
			
BCLIGHT-033	BCLIGHT-034	BCLIGHT-035	BCLIGHT-036
			
BCLIGHT-037	BCLIGHT-038	BCLIGHT-039	BCLIGHT-040

